

## ***Marine Paint Manual***

Reference No. : E 10/16

Issue Date: February 2019 (EU)

### **NIPPON O-MARINE FINISH (E) WHITE**

A finish for the interior and exterior of superstructures and decks containing weathering resistant alkyd resin as a binder which provides good workability.

Suitable Use	Finish for interior and exterior of superstructures, decks, etc.						
Type	Alkyd						
Color (Product Code)*	White	(SKK 9010)*	*Not color code (See note 6)				
Gloss	Gloss						
Volume Solids	48 ± 2% (ISO3233:1998)						
Typical Dry Film Thickness	40 μm						
Approx. Wet Film Thickness	85 μm						
Theoretical Coverage	12.00 m <sup>2</sup> / L (40 μm)						
Drying Time	Surface Dry	8 hours (5°C)	3 hours (20°C)	2 hours (30°C)			
	Dry Hard	24 hours (5°C)	12 hours (20°C)	10 hours (30°C)			
Interval before Overcoating ( by self )	Min.	24 hours (5°C)	12 hours (20°C)	10 hours (30°C)			
	Max.	— (5°C)	— (20°C)	— (30°C)			
Thinner (Code. No.)	NIPPON MARINE THINNER 100 (VSK 23) / 0 ~ 5%, by volume						
Application Method	Airless Spray	Tip range	0.38 ~ 0.48 mm (0.015" - 0.019")				
		Fan angle	45 ~ 69°				
		Output pressure	100 ~ 150 kg/cm <sup>2</sup>				
	Brush / Roller	For touching up small areas only					
Package	20L						
Flash Point	26°C						
Surface Preparation	All surfaces to be coated should be clean, dry and free from contamination.						
	High pressure fresh water wash and remove all oil / grease, soluble contaminants and other foreign matters.						
Generals	For commercial use only. Attention - Avoid exposure - obtain special instructions before use.						
Safety	Take precautions to avoid skin and eye contact (i.e. gloves, goggles, face masks, barrier creams etc.)						
	Proper ventilation and protective measures must be provided during applications and drying period to keep solvent vapor concentrations within safe limits.						
	Prior to use, obtain, consult and follow the SDS for this product concerning health and safety information.						

---

## ***Marine Paint Manual***

NIPPON O-MARINE FINISH (E) WHITE

Issue Date: February 2019 (EU)

<Note>

- 1) The information contained in this sheet is liable to modification from time to time in the light of experience and our policy of continuous product development.
- 2) Use NON-SLIP SAND to produce a nonslip surface for decks and walkways.
- 3) The following colors are available as our standard. (on request)
- 4) Store the paints in paint store.
- 5) Various colour shall be available.
- 6) This code is internal product code of NPMEU. Please be careful as it isn't color code.