

## DRAFT A/F SUPER

A special metal acrylate antifouling, designed for draft marks, provides good antifouling performance. It is applicable to general ocean-going vessels and coastal vessels.

Suitable Use	Anti-fouling for draft marks				
Type	Special metal acrylate resin ( Tin-free / Self-polishing / Hydrolysis )				
Color	White, Black				
Gloss	Semi-gloss				
Volume Solids	44 ± 2% (ISO3233:1998)				
Typical Dry Film Thickness	50 ~ 80 μm				
Approx. Wet Film Thickness	114 ~ 182 μm				
Theoretical Coverage	8.5 m <sup>2</sup> / L (50 μm)				
Drying Time	Surface Dry	1 hour (5°C)	40 minutes (20°C)	30 minutes (30°C)	
	Dry Hard	3 hours (5°C)	1 hour (20°C)	40 minutes (30°C)	
Interval before Overcoating ( by self )	Min.	6 hours (5°C)	4 hours (20°C)	3 hours (30°C)	
	Max.	— (5°C)	— (20°C)	— (30°C)	
Interval before Immersion (100 μm)	Min.	12 hours (5°C)	6 hours (20°C)	5 hours (30°C)	
	Thinner	NIPPON MARINE THINNER 200 ( 0 ~ 5%, by weight )			
Application Method	Brush / Roller				
Typical Package	3.5 kg, 20 kg				
	Package may vary from country to country.				
Japan Local Brand	DRAFT A/F SUPER				
Flash Point	24 °C				

**Surface Preparation** All surfaces to be coated should be clean, dry and free from contamination.  
High pressure fresh water wash and remove all oil / grease, soluble contaminants and other foreign matters.

**Safety** Take precautions to avoid skin and eye contact (i.e. gloves, goggles, face masks, barrier creams etc.)  
Proper ventilation and protective measures must be provided during applications and drying period to keep solvent vapor concentrations within safe limits.  
Prior to use, obtain, consult and follow the SDS for this product concerning health and safety information.

### <Note>

- 1) The information contained in this sheet is liable to modification from time to time in the light of experience and our policy of continuous product development.
- 2) The declaration letter of Tin-free Antifouling Paint would not be issued if mixed with the other antifouling paints product or another chemical products.
- 3) Store the paints in paint store.